



SOILKEE PASTURE RENOVATOR

MODEL SERIES SKR3000

Patented hybrid cultivation, aeration and seasonal multi-species seeding platform for soil improvement on medium sized farms.

TECHNICAL SPECIFICATIONS

Market:	Dairy and Livestock
Connection type:	Linkage
PTO:	1 3/8 " 6 spline PTO with slip clutch.
PTO HP:	120-150HP
Working width (mm):	3000
Product weight (kg):	1500
Height / width / length (mm):	2100, 3280, 1100
Cultivated area:	17%
Shaft:	Horizontal and heavy duty
Gearbox:	Right angle
Geardrive:	4 Gear drive
Rotor:	7 discs with 6 blades per disc and 75 mm depth
Frame:	High strength steel
Seed hopper construction:	Food grade 316 stainless steel
Seed hopper capacity:	970 L
Seed feeders:	7 gravity fed
Seed feed:	Variable
Safety guards:	On all PTO shafts
Hitch:	Cat 2 hitch
Bearings:	Twin row roller bearings
Mounting system:	3-point linkage
Paint:	2-pack automotive
Structural warranty:	12 Months
Gearbox Warranty:	12 Months
Contractor Warranty:	3 Months

FURTHER INFORMATION

Niels Olsen, Founder and CEO Soilkee Pty Ltd

T: +61 3 5627 5526 : M: +61 407 337 560

E: npo@soilkee.com.au : W: www.soilkee.com.au

