

# SOILKEE MULCHER



## MODEL SERIES SKM3000

3m Flail Mower with front & rear linkage and hydraulic offset.

## TECHNICAL SPECIFICATIONS

Market:	Dairy and Livestock
Connection type:	3 Point Linkage cat. 2
Mounting:	Universal front and rear linkage
PTO:	1 3/8 " 6 spline PTO.
PTO HP:	80-100 HP
RPM:	540 or 1000
Working width (mm):	3000
Product weight (kg):	1200
Height / width / length (mm):	1120, 3200, 1530
Rotor diameter: (mm)	220
Gearbox:	Right angle, heavy duty, internal free wheel
Belt-drive:	5 Belts
Belt tension:	Automatic belt tightener.
Blades:	60 wide blades
Frame:	High strength steel
Cutting height adjustment:	Adjustable skids and height roller.
Safety guards:	On all PTO shafts
Bearings:	Tapered lock roller bearings
Structural warranty:	12 Months
Gearbox Warranty:	12 Months
Contractor Warranty:	3 Months

## FURTHER INFORMATION

Niels Olsen, Founder and CEO Soilkee Pty Ltd

T: +61 3 5627 5526 : M: +61 407 337 560

E: [npo@soilkee.com.au](mailto:npo@soilkee.com.au) : W: [www.soilkee.com.au](http://www.soilkee.com.au)